

PAGE: 1

PRINT DATE: 03/31/94

FAILURE MODES EFFECTS ANALYSIS (FMEA) - CRITICAL HARDWARE

NUMBER: 01-5B-390122-X

SUBSYSTEM NAME: PURGE, VENT & DRAIN - ACTRS

REVISION: 1

03/30/94

	PART NAME VENDOR NAME	PART NUMBER VENDOR NUMBER
LRU	: DOOR DRIVE ACTUATOR ELLANEF	MC147-0007
SRU	: ELECTRIC MOTOR/BRAKE	A1063A010

PART DATA

EXTENDED DESCRIPTION OF PART UNDER ANALYSIS:

ELECTRIC MOTOR/BRAKE, DOOR DRIVE ACTUATOR, VENTS 3, 5 OR 6 (PLB)

QUANTITY OF LIKE ITEMS: 12

(6 RH & 6 LH)

(1 PER MOTOR; 2 PER ACTR)

FUNCTION:

TO PROVIDE POWER FOR THE ACTUATOR TO CYCLE THE VENT DOOR (OPEN OR CLOSED).

**FAILURE MODES EFFECTS ANALYSIS (FMEA) - CRITICAL FAILURE MODE
NUMBER: 01-5B-380122-03**

REVISION# 1 03/30/94

SUBSYSTEM NAME: PURGE, VENT, & DRAIN - ACTRS
LRU: DOOR DRIVE ACTUATOR
ITEM NAME: ELECTRIC MOTOR/BRAKE

CRITICALITY OF THIS
FAILURE MODE: 1R3

FAILURE MODE:
BRAKE FAILS TO ENGAGE

MISSION PHASE:
DO DE-ORBIT

VEHICLE/PAYLOAD/KIT EFFECTIVITY: 102 COLUMBIA
103 DISCOVERY
104 ATLANTIS
105 ENDEAVOUR

CAUSE:
ADVERSE TOLERANCES/WEAR, CONTAMINATION/FOREIGN OBJECT/DEBRIS, DEFECTIVE PART/MATERIAL OR MANUFACTURING DEFECT, FAILURE/DEFLECTION OF INTERNAL PART, ELECTRICAL FAILURE (SHORT CIRCUIT, ETC.)

CRITICALITY 1/1 DURING INTACT ABORT ONLY? NO

REDUNDANCY SCREEN A) PASS
B) FAIL
C) PASS

PASS/FAIL RATIONALE:

- A) _____
- B) FAILS REDUNDANCY SCREEN "B" SINCE NORMAL FUNCTION IS PERFORMED WITH DUAL MOTOR OPERATION.
- C) _____

- FAILURE EFFECTS -

(A) SUBSYSTEM:
FIRST FAILURE OF A MOTOR OR BRAKE ON SAME SHAFT - NO EFFECT.

(B) INTERFACING SUBSYSTEM(S):
FIRST FAILURE NO EFFECT

(C) MISSION:
FIRST FAILURE NO EFFECT

(D) CREW, VEHICLE, AND ELEMENT(S):
FIRST FAILURE NO EFFECT

**FAILURE MODES EFFECTS ANALYSIS (FMEA) - CRITICAL FAILURE MODE
NUMBER: 01-5B-380122-03****(E) FUNCTIONAL CRITICALITY EFFECTS:**

SECOND FAILURE OF THE REMAINING MOTOR OR BRAKE ON SAME SHAFT - LOSS OF FUNCTION: REDUNDANT MOTOR WILL BACKDRIVE THROUGH THE DIFFERENTIAL AND FUNCTION WILL BE LOST. POSSIBLE LOSS OF MISSION/CREW/VEHICLE AFTER THIRD FAILURE (OPPOSITE VENT DOOR FAILS CLOSED) DUE TO LOSS OF VENTING CAPABILITY WHICH MAY RESULT IN STRUCTURAL OVERLOAD ON ENTRY DUE TO PRESSURE DIFFERENTIAL. LOCALIZED THERMAL DAMAGE ONLY, IF A DOOR IS FAILED OPEN DURING ENTRY; THERMAL ANALYSIS (SAS-TA-RCC-78-152, -79-012 AND -79-065) SHOWS THAT CREW AND VEHICLE WILL SURVIVE.

-DISPOSITION RATIONALE-

(A) DESIGN:

THE VENT DOOR SUBSYSTEM CONSISTS OF SEALED DOORS INTO THE FUSELAGE CAVITIES (THAT ARE OPENED OR CLOSED TO REGULATE INTERNAL PRESSURE) AND ARE POSITIONED BY ELECTROMECHANICAL DOOR DRIVE ACTUATORS CONNECTED TO TORQUE TUBES, BELLCRANKS AND CONNECTING-RODS. EACH VENT DOOR ACTUATOR CONSISTS OF A PLANETARY GEARBOX/DIFFERENTIAL AND A SPRING-LOADED (4) BALL-DETENT TORQUE LIMITER DRIVEN BY TWO (REDUNDANT) 3-PHASE ELECTRIC MOTORS. EACH MOTOR HAS AN INTEGRAL SPRING-LOADED FRICTION BRAKE; WITH LIMIT SWITCHES, SOFT (LEAF SPRING) STOPS AND HARD MECHANICAL STOPS TO CONTROL/LIMIT ACTUATOR MOVEMENT/ROTATION. THE ACTUATOR HOUSING IS FABRICATED OF 6AL-4V TI AND DESIGNED TO PRECLUDE THE ENTRY OF FOREIGN PARTICLES. GEARS MADE OF PH13-8M0 AND 15-5PH CRES; 4340 AND 9Ni-4Co. 2CSTL. BEARINGS MADE OF 440 AND OTHER CRES. PARTS ARE CLEANED TO LEVEL 300, PER MA0110-301 (PRIOR TO ASSEMBLY); ASSEMBLED IN A CLASS 100,000 CLEAN ROOM (PER FED-STD-209). DUAL ROTATING SURFACES ON BEARINGS. SAFETY FACTOR 1.4 MINIMUM. PROVISION EXISTS TO CYCLE THE ACTUATOR (TO LOOSEN A STALLED/JAMMED MECHANISM). BRAKES MUST BE ELECTRICALLY ENERGIZED TO DISENGAGE AND ARE DESIGNED TO FAIL IN THE ENGAGED POSITION. DIFFERENTIAL IS DESIGNED TO DISTRIBUTE POWER FROM EITHER ONE OR BOTH (REDUNDANT) MOTORS. MOTORS ARE DESIGNED TO OPERATE IN AN EMERGENCY 2-PHASE CONDITION. THE TORQUE LIMITER IS DESIGNED TO PROTECT BOTH MOTORS AND THE DRIVE TRAIN FROM AN OVERLOAD FAILURE.

(B) TEST:

QUALIFICATION TESTS: QUAL-CERTIFIED PER CR-28-147-0007-0006. QUALIFICATION TESTS INCLUDE: HUMIDITY TEST (PER MIL-STD-810B), SHOCK TEST (PER MIL-STD-810, PROCEDURE I, METHOD 516.1), THERMAL VACUUM TEST (0.000001 TORR FOR 55 HOURS, WITH TEMPERATURE CYCLED BETWEEN -100 DEG F AND +330 DEG F, AND ACTUATOR CYCLED), THERMAL CYCLE TEST (TEMPERATURE CYCLED BETWEEN -100 DEG F AND +330 DEG F; INCLUDES MOTOR 1 AND MOTOR 2 CYCLED 500 TIMES EACH, ALONE, AND WITHIN 10 SEC/DIRECTION UNDER LOAD FROM CLOSE-OPEN-CLOSE; 750 CYCLES WITH BOTH MOTORS AT 5 SEC/DIRECTION FROM CLOSE-OPEN-CLOSE; AND 250 CYCLES WITH BOTH MOTORS FROM CLOSE-OPEN-INTERMEDIATE-CLOSE) AND MECHANICAL STOPS TEST (ACTUATOR OPERATED AT FULL RATE AND WITH NO LOAD OR BRAKES, 100 TIMES IN EACH DIRECTION). POWER CONSUMPTION TEST, FREEPLAY TEST AND IRREVERSIBILITY TEST WERE CONDUCTED AS DEFINED IN THE ACCEPTANCE TESTS. CERTIFICATION BY ANALYSIS/SIMILARITY INCLUDED: QUAL-ACCEPTANCE VIBRATION TEST (QAVT) (ACOUSTIC VIBRATIONS FROM 20-2,000 HZ; PER MF0004-32), FLIGHT VIBRATION TEST (20-2,000 HZ), FUNGUS, OZONE, SALT SPRAY, SAND/DUST,

**FAILURE MODES EFFECTS ANALYSIS (FMEA) - CRITICAL FAILURE MODE
NUMBER: 01-5B-380122-03**

TRANSPACKAGE, ACCELERATION, LANDING SHOCK, MARGIN OF SAFETY AND EXPLOSIVE ATMOSPHERE.

ACCEPTANCE TESTS: INCLUDES EXAMINATION OF PRODUCTS (FOR WEIGHT, DIMENSIONS, CONSTRUCTION, CLEANLINESS AND FINISH), ACCEPTANCE VIBRATION TESTS (AVT) (20-2,000 HZ, 30 SEC TO 5 MINUTES, IN EACH OF THREE ORTHOGONAL AXES; WITH ELECTRICAL CIRCUITS MONITORED FOR CONTINUITY), ACCEPTANCE THERMAL TESTS (ATT) (CYCLED BETWEEN -150 DEG F AND +310 DEG F; MOTOR 1, MOTOR 2 AND DUAL MOTOR), POWER CONSUMPTION TEST (OPERATED AT RATED LOAD, SINGLE MOTOR DEPLOYED WITHIN 10 SEC, DUAL MOTORS DEPLOYED WITHIN 5 SEC, 115 WATTS/MOTOR MAXIMUM, 400% MAXIMUM STARTING CURRENT AT RATED LOAD), INSULATION RESISTANCE TEST AND DIELECTRIC STRENGTH TEST (PER MF0004-002), CYCLING TEST (SINGLE MOTOR, 20 CYCLES EACH FROM CLOSE-OPEN-CLOSE AT 10 SEC/DIRECTION; DUAL MOTOR, 40 CYCLES FROM CLOSE-OPEN-CLOSE AT 5 SEC/DIRECTION; DUAL MOTOR, 20 CYCLES FROM INTERMEDIATE-OPEN-CLOSE), FREEPLAY TEST (MAXIMUM ANGULAR FREEPLAY AT OUTPUT SHAFT +/-0.015 DEGREES, WITH 10.0 INCH-LB REVERSING TORQUE), STALL/MAXIMUM TORQUE TEST (STALL/MAXIMUM OUTPUT NOT TO EXCEED 1.5 TIMES MAX OPERATING TORQUE OF 670 INCH-LB), IRREVERSIBILITY TEST (ACTUATOR MUST BE IRREVERSIBLE TO THE MAXIMUM OPERATING LOAD IN EITHER DIRECTION), MECHANICAL LIMITS TEST AND ELECTRICAL LIMITS TEST (ACTUATOR AND OUTPUT ARM CYCLED FULL TRAVEL TO VERIFY COMPLIANCE WITH MECHANICAL AND ELECTRICAL LIMITS).

GROUND TURNAROUND TEST:

ANY TURNAROUND CHECKOUT TESTING IS ACCOMPLISHED IN ACCORDANCE WITH OMRSD.

(C) INSPECTION:**RECEIVING INSPECTION**

MATERIAL AND PROCESS CERTIFICATIONS ARE VERIFIED BY INSPECTION. ALL PURCHASED PART DATA PACKAGES ARE VERIFIED BY INSPECTION.

CONTAMINATION CONTROL

PARTS ARE CLEANED TO A 300 LEVEL PER MA0110-301 IS VERIFIED BY INSPECTION. ASSEMBLY IN A CLASS 100,000 CLEAN ROOM PER FED-STD-209.

ASSEMBLY/INSTALLATION

TORQUE LIMITER ASSEMBLY IS VERIFIED BY INSPECTION. BEARING INSTALLATION, SPRING DIAMETERS AND SPRING FORCE ARE VERIFIED BY INSPECTION.

NONDESTRUCTIVE EVALUATION

STRUCTURAL INTEGRITY VERIFIED BY PENETRANT OR MAGNETIC PARTICLE INSPECTION. TECHNIQUES AND TECHNICIANS ARE CERTIFIED.

TESTING

ATP IS VERIFIED BY INSPECTION.

HANDLING/PACKAGING

HANDLING AND PACKAGING REQUIREMENTS ARE VERIFIED BY INSPECTION.

(D) FAILURE HISTORY:

CURRENT DATA ON TEST FAILURES, FLIGHT FAILURES, UNEXPLAINED ANOMALIES, AND OTHER FAILURES EXPERIENCED DURING GROUND PROCESSING ACTIVITY CAN BE FOUND IN THE PRACA DATABASE.

**FAILURE MODES EFFECTS ANALYSIS (FMEA) - CRITICAL FAILURE MODE
NUMBER: 01-5B-380122-03**

(E) OPERATIONAL USE:
NONE.

- APPROVALS -

PAE MANAGER	: K. L. PRESTON	: <i>K.L. Preston 4/6/94</i>
PRODUCT ASSURANCE ENG.	: T. AI	: <i>T. AI</i>
DESIGN ENGINEERING	: A. P. YSON	: <i>PAE Yson 4/15/94</i>
NASA SSMA	:	: <i>W.H. [unclear] 7/6/94</i>
NASA SUBSYSTEM MANAGER	:	: <i>R.E. [unclear] 7/6/94</i>