

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL HARDWARE****NUMBER: 03-1-0310 -X****SUBSYSTEM NAME:** MAIN PROPULSION**REVISION:** 2 08/02/00**PART DATA**

	<b>PART NAME</b>	<b>PART NUMBER</b>
	<b>VENDOR NAME</b>	<b>VENDOR NUMBER</b>
LRU	:LO2 INBOARD 8" FILL/DRAIN VALVE (PV10) UNITED SPACE ALLIANCE - NSLD	MC284-0397-0030 74328000-157

**EXTENDED DESCRIPTION OF PART UNDER ANALYSIS:**

FILL INBOARD LO2 VALVE, 8 INCH, PNEUMATICALLY OPERATED, INCLUDES A RELIEF VALVE.

VALVE WAS ORIGINALLY DESIGNED AND MANUFACTURED BY FAIRCHILD CONTROLS BUT IS NOW MANUFACTURED BY UNITED SPACE ALLIANCE-NSLD AS AN ALTERNATE PRODUCTION AGENCY.

**REFERENCE DESIGNATORS:** PV10**QUANTITY OF LIKE ITEMS:** 1**FUNCTION:**

PROVIDES A MEANS OF LOADING AND DRAINING THE ET THROUGH THE PROPELLANT FEED SYSTEM. THE VALVE, ALONG WITH THE OUTBOARD FILL AND DRAIN VALVE (PV9), PROVIDES A REDUNDANT MEANS OF CONTAINING PROPELLANT IN THE FEED SYSTEM. THE VALVE IS MOUNTED ON THE FEED LINE MANIFOLD TO ISOLATE THE FILL LINE FROM THE FEED SYSTEM. THE VALVE IS CLOSED AFTER LOADING IN ORDER TO DRAIN THE FILL LINE (PRIOR TO CLOSING THE OUTBOARD FILL & DRAIN VALVE). BOTH THE INBOARD AND OUTBOARD VALVES REMAIN CLOSED DURING ENGINE OPERATION AND ARE OPENED FOR MPS VACUUM INERT TO VENT LO2 RESIDUALS. BOTH VALVES ARE OPEN FOR LO2 DUMP IN RTLS AND TAL ABORTS. THE INBOARD VALVE REMAINS OPEN AFTER DUMP/INERT, THROUGH REENTRY AND LANDING. THE VALVE INCORPORATES AN ANTI-SLAM MECHANISM TO PREVENT SLAMMING DAMAGE DURING IMPROPER VALVE OPEN/CLOSE OPERATIONS. THE VALVE INCORPORATES A RELIEF VALVE, RELIEVING FROM THE FILL LINE INTO THE MANIFOLD; AND A PORT FOR INSTALLATION OF LO2 RELIEF SHUTOFF ISOLATION VALVE (PV7).

**FAILURE MODES EFFECTS ANALYSIS FMEA -- CIL FAILURE MODE**

**NUMBER: 03-1-0310-08**

**REVISION#: 2 08/02/00**

**SUBSYSTEM NAME:** MAIN PROPULSION

**LRU:** LO2 INBOARD 8" FILL AND DRAIN VALVE (PV10)

**CRITICALITY OF THIS**

**ITEM NAME:** LO2 INBOARD 8" FILL AND DRAIN VALVE (PV10)

**FAILURE MODE:** 1R2

---

**FAILURE MODE:**

RELIEF VALVE REVERSE LEAKAGE DURING ASCENT.

**MISSION PHASE:** LO LIFT-OFF

<b>VEHICLE/PAYLOAD/KIT EFFECTIVITY:</b>	102	COLUMBIA
	103	DISCOVERY
	104	ATLANTIS
	105	ENDEAVOUR

**CAUSE:**

PIECE PART STRUCTURAL FAILURE, BINDING, CONTAMINATION

**CRITICALITY 1/1 DURING INTACT ABORT ONLY?** NO

---

<b>REDUNDANCY SCREEN</b>	A) PASS
	B) FAIL
	C) PASS

**PASS/FAIL RATIONALE:**

A)

B)

NO ABILITY TO DETECT LEAKAGE PAST RELIEF VALVE

C)

---

**- FAILURE EFFECTS -**

---

**(A) SUBSYSTEM:**

FIRST FAILURE – NO EFFECT.

**(B) INTERFACING SUBSYSTEM(S):**

SAME AS A.

**(C) MISSION:**

SAME AS A.

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0310-08**

**(D) CREW, VEHICLE, AND ELEMENT(S):**

SAME AS A.

**(E) FUNCTIONAL CRITICALITY EFFECTS:**

1R/2 2 SUCCESS PATHS. TIME FRAME - ASCENT.

- 1) RELIEF VALVE FAILS TO RESEAT/REVERSE LEAKAGE.
- 2) OUTBOARD FILL & DRAIN (PV9) FAILS TO REMAIN CLOSED.

RESULTS IN THE OVERBOARD LEAKAGE OF LO2. FIRE HAZARD AT THE VEHICLE EXTERIOR.  
POSSIBLE LOSS OF CREW/VEHICLE.

---

**-DISPOSITION RATIONALE-**

---

**(A) DESIGN:**

DURING CERTIFICATION TESTING THE RELIEF VALVE WAS CYCLED 5000 TIMES (2500 EACH AT AMBIENT AND CRYOGENIC TEMPERATURES). LEAKAGE IN BOTH DIRECTIONS WAS MEASURED AFTER EACH 500 CYCLES. THE WORST CASE WAS 63 SCIMS OF GHE IN THE REVERSE DIRECTION - WELL WITHIN SPEC. RELIEF VALVE LEAKAGE WILL NOT CAUSE EARLY OXIDIZER DEPLETION SINCE LEAKAGE OVERBOARD WILL BE LESS THAN 33 GALLONS. THE RELIEF VALVE IS OF SIMPLE DESIGN CONSISTING OF ONLY SEVEN PARTS. A SPHERICAL (BALL) POPPET IS SPRING LOADED ONTO A KEL-F SEAT AND IS CLOSELY GUIDED THROUGHOUT ITS SHORT STROKE. TO FURTHER PREVENT BINDING, ALL SURFACES IN CONTACT WITH THE ALUMINUM-OXIDE POPPET ARE HARD ANODIZED 6061-T651.

**(B) TEST:**

ATP

ANTI-SLAM VALVES (BEFORE ASSEMBLY INTO THE ACTUATOR) - EXAMINATION OF PRODUCT; AMBIENT PROOF (1275 PSIG); AMBIENT AND CRYO FLOW; AMBIENT AND CRYO CRACKING PRESSURE; POST TEST EXAMINATION.

ACTUATOR (BEFORE ASSEMBLY ONTO THE FILL AND DRAIN VALVE) - EXAMINATION OF PRODUCT; POSITION INDICATION; AMBIENT PROOF (1275); ELECTRICAL CHARACTERISTICS; AMBIENT EXTERNAL LEAKAGE.

RELIEF VALVE ASSEMBLY (BEFORE INSTALLATION INTO THE FILL & DRAIN VALVE)- EXAMINATION OF THE PRODUCT; AMBIENT PROOF (340 PSIG); AMBIENT AND CRYO CRACK/RESEAT (15-50 PSID) AND INTERNAL LEAKAGE; POST TEST EXAMINATION.

FILL AND DRAIN VALVE ASSEMBLY -

EXAMINATION OF PRODUCT

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0310-08**

ELECTRICAL BONDING

AMBIENT PROOF WITH VALVE OPEN (358 PSIG) AND CLOSED (275 PSID) APPLIED AT INBOARD SIDE

CRYO PROOF WITH VALVE OPEN (358 PSIG) AND CLOSED (358 PSID) APPLIED AT INBOARD SIDE

AMBIENT AND CRYO EXTERNAL LEAKAGE OF VALVE BODY (270 PSIG)

CRYO EXTERNAL LEAKAGE OF ACTUATOR (740 PSIG)

AMBIENT AND CRYO RESPONSE TIME (NORMAL AT 400 AND 740 PSIG ACTUATOR PRESSURE, AND SLAM AT 740 PSIG)

AMBIENT AND CRYO ACTUATOR LEAKAGE FROM PORT TO PORT

AMBIENT AND CRYO VALVE SHAFT SEAL (PRIMARY AND SECONDARY) LEAKAGE WITH 270 PSID ACROSS THE SEAL

AMBIENT AND CRYO VALVE INTERNAL LEAKAGE (INLET-TO-OUTLET WITH 15 PSID, OUTLET-TO-INLET WITH 270 PSID)

AMBIENT AND CRYO RELIEF VALVE CRACK AND RESEAT (15 TO 50 PSID)

POST TEST EXAMINATION

CERTIFICATION

STRUCTURAL LOAD AT CRYO TEMPS (-300 DEG F) (AXIAL, SHEAR, TORSION, BENDING) WITH THE VALVE IN TENSION, PERFORM VALVE RESPONSE TIME (NOMINAL AND SLAM) ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), RELIEF VALVE CRACK AND RESEAT, AND EXTERNAL LEAKAGE (BODY AND ACTUATOR) TESTS. REPEAT WITH THE VALVE IN COMPRESSION.

VALVE LIFE CYCLING:

2400 CYCLES AT AMBIENT TEMPERATURE WITH 5 PSIG INTERNAL PRESSURE (525 NORMAL CYCLES AND 1875 SLAM CYCLES)

100 AMBIENT CYCLES (50 NORMAL AND 50 SLAM CYCLES) WITH VALVE INLET VENTED TO ATMOSPHERE AND VALVE OUTLET CONNECTED TO A 4 CUBIC FOOT VOLUME PRESSURIZED TO 220 PSIG WITH GO2

2400 CRYO TEMPERATURE (-300 DEG F) CYCLES WITH 220 PSIG INTERNAL PRESSURE (1775 NORMAL CYCLES AND 625 SLAM CYCLES)

100 NORMAL CRYO CYCLES WITH THE VALVE INLET VENTED TO ATMOSPHERE AND THE OUTLET PRESSURIZED TO 220 PSIG

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0310-08**

FOR THE FOREGOING LIFE TEST, PRIOR TO AND EVERY 100 CYCLES THEREAFTER, ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, AND VALVE INTERNAL LEAKAGE (OUTLET-TO-INLET) TESTS WERE PERFORMED.

RELIEF VALVE LIFE CYCLING :

2500 CYCLES AT CRYO (-300 DEG F) TEMP, 2500 CYCLES AT AMBIENT.

FOLLOWING EACH 500 CYCLES PERFORM FILL AND DRAIN VALVE INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), AND CRACK/RESEAT TESTS. POST CYCLE EXAMINATION.

VIBRATION:

PRE-VIBRATION TESTS -

VALVE RESPONSE TIME (NORMAL AND SLAM), ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), CRACK AND RESEAT, AND EXTERNAL LEAKAGE (BODY AND ACTUATOR)

TRANSIENT SINUSOIDAL VIBRATION -

270 PSIG AND -250 DEG F IN EACH AXIS

RANDOM VIBRATION TESTS -

13.3 HOURS IN EACH OF THREE AXES WITH VALVE CLOSED AND AT -250 DEG F MAXIMUM. HALF OF THE TIME THE VALVE INTERNAL PRESSURE IS 270 PSIG; THE OTHER HALF AT 5 PSIG. ONCE EACH HOUR, CLOSING PRESSURE IS REMOVED FROM THE ACTUATOR. ALSO BOTH CLOSING AND OPENING PRESSURES ARE APPLIED CONCURRENTLY TO THE ACTUATOR. IN BOTH CASES THE VALVE REMAINS CLOSED

DESIGN SHOCK: 18 SHOCKS OF 15G EACH - THREE IN EACH DIRECTION ALONG EACH OF THREE AXES, ALL WITH VALVE OPEN AND ACTUATOR VENTED

DESIGN SHOCK POST TEST:

AMBIENT - VALVE RESPONSE, INTERNAL AND EXTERNAL LEAKAGES

CRYO - VALVE RESPONSE, INTERNAL AND EXTERNAL LEAKAGES

ELECTRICAL CHARACTERISTICS; POSITION INDICATION

BURST: 413 PSIG VALVE OPEN 413 PSIG ON OUTLET OF CLOSED VALVE, 1700 PSIG ACTUATOR

GROUND TURNAROUND TEST

ANY TURNAROUND CHECKOUT IS ACCOMPLISHED IN ACCORDANCE WITH OMRSD.

**(C) INSPECTION:**

RECEIVING INSPECTION

RAW MATERIALS ARE VERIFIED BY INSPECTION FOR MATERIAL AND PROCESS CERTIFICATION. BODY HOUSING FORGING IS ULTRASONICALLY AND PENETRANT INSPECTED.

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0310-08**

**CONTAMINATION CONTROL**

PARTS ARE VERIFIED CLEAN TO LEVEL 800A. THE ACTUATOR IS CLEANED TO 400A.

**ASSEMBLY/INSTALLATION**

ALL PARTS ARE PROTECTED FROM DAMAGE AND CONTAMINATION. LOG OF CLEAN ROOM AND TOOL CALIBRATION ARE VERIFIED BY INSPECTION. ALL SURFACES REQUIRING CORROSION PROTECTION ARE VERIFIED. VISUAL (3X TO 7X) AND DIMENSIONAL INSPECTION OF VALVE BODY AND COMPONENTS ARE VERIFIED DURING ASSEMBLY. THREADED FASTENER TORQUES ARE VERIFIED BY INSPECTION. MANDATORY INSPECTION POINTS ARE INCLUDED IN THE ASSEMBLY PROCEDURE.

**CRITICAL PROCESSES**

HEAT TREATMENT AND DRY FILM LUBE APPLICATION ARE VERIFIED BY INSPECTION.

**NON DESTRUCTIVE EVALUATION**

VALVE BODY, PRIOR TO FINAL MACHINING, IS SUBJECTED TO DYE PENETRANT INSPECTION. REQUIREMENTS FOR DETAIL PARTS PENETRANT INSPECTION ARE BASED UPON CONFIGURATION, MATERIAL, AND MANUFACTURING PROCESSES.

**TESTING**

ACCEPTANCE TEST VERIFIED BY INSPECTION.

**HANDLING/PACKAGING**

PACKAGING FOR SHIPMENT VERIFIED BY INSPECTION.

**(D) FAILURE HISTORY:**

THE RELIEF VALVE EXPERIENCED LEAKAGE (CAR AB3307) DURING QUALIFICATION TESTING DUE TO INSUFFICIENT CLEARANCE BETWEEN SPRING GUIDE AND BODY. THIS WAS CORRECTED BY MINOR DIMENSIONAL CHANGES TO THE CHAMFER ON THE SPRING GUIDE AND INCREASING THE BODY DIAMETER PERMITTING PROPER BALL SEATING.

CURRENT DATA ON TEST FAILURE, FLIGHT FAILURE, UNEXPLAINED ANOMALIES, AND OTHER FAILURES EXPERIENCED DURING GROUND PROCESSING ACTIVITY CAN BE FOUND IN THE PRACA DATABASE.

**(E) OPERATIONAL USE:**

NO CREW ACTION CAN BE TAKEN.

---

**- APPROVALS -**

---

S&R ENGINEERING	: W.P. MUSTY	: /S/ W. P. MUSTY
S&R ENGINEERING ITM	: P. A. STENGER-NGUYEN	: /S/ P. A. STENGER-NGUYEN
DESIGN ENGINEERING	: STUART KOBATA	: /S/ STUART KOBATA
MPS SUBSYSTEM MGR.	: TIM REITH	: /S/ TIM REITH
MOD	: BILL LANE	: /S/ BILL LANE
USA SAM	: MIKE SNYDER	: /S/ MIKE SNYDER

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0310-08**

USA ORBITER ELEMENT	: SUZANNE LITTLE	: /S/ SUZANNE LITTLE
NASA SR&QA	: BILL PRINCE	: /S/ BILL PRINCE