

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL HARDWARE**

NUMBER: 03-1-0311 -X

SUBSYSTEM NAME: MAIN PROPULSION

REVISION: 4 08/01/00

**PART DATA**

	<b>PART NAME</b>	<b>PART NUMBER</b>
	<b>VENDOR NAME</b>	<b>VENDOR NUMBER</b>
LRU	: LO2 OUTBOARD 8" FILL/DRAIN VALVE (PV9) UNITED SPACE ALLIANCE - NSLD	MC284-0397-0029 74328000-155

**EXTENDED DESCRIPTION OF PART UNDER ANALYSIS:**

LO2 OUTBOARD FILL VALVE, 8 INCH, PNEUMATICALLY OPERATED.

VALVE WAS ORIGINALLY DESIGNED AND MANUFACTURED BY FAIRCHILD CONTROLS BUT IS NOW MANUFACTURED BY UNITED SPACE ALLIANCE-NSLD AS AN ALTERNATE PRODUCTION AGENCY.

REFERENCE DESIGNATORS: PV9

QUANTITY OF LIKE ITEMS: 1

**FUNCTION:**

PROVIDES A MEANS OF LOADING AND DRAINING THE ET THROUGH THE PROPELLANT FEED SYSTEM. THE OUTBOARD VALVE, ALONG WITH THE INBOARD FILL AND DRAIN VALVE (PV10), PROVIDES A REDUNDANT MEANS OF CONTAINING PROPELLANT IN THE FEED SYSTEM. THE VALVE IS MOUNTED ON THE FILL AND DRAIN DISCONNECT AND IS CLOSED PRIOR TO ENGINE START. BOTH THE INBOARD AND OUTBOARD VALVES REMAIN CLOSED DURING ENGINE OPERATION AND ARE OPENED FOR MPS VACUUM INERT TO VENT LO2 RESIDUALS. BOTH VALVES ARE OPEN FOR LO2 DUMP IN RTLS AND TAL ABORTS. THE OUTBOARD VALVE IS CLOSED FOR REENTRY MANIFOLD REPRESSURIZATION. INCORPORATES AN ANTI-SLAM MECHANISM TO PREVENT SLAMMING DAMAGE DURING IMPROPER VALVE OPEN/CLOSE OPERATIONS. THE VALVE ALSO INCORPORATES A RELIEF VALVE, RELIEVING INTO THE FILL LINE.

**FAILURE MODES EFFECTS ANALYSIS FMEA -- CIL FAILURE MODE**

**NUMBER: 03-1-0311-04**

**REVISION#: 4 08/01/00**

**SUBSYSTEM NAME: MAIN PROPULSION**

**LRU: LO2 OUTBOARD 8" FILL/DRAIN VALVE (PV9)**

**ITEM NAME: LO2 OUTBOARD 8" FILL/DRAIN VALVE (PV9)**

**CRITICALITY OF THIS**

**FAILURE MODE: 1R2**

**FAILURE MODE:**

FAILS TO REMAIN CLOSED/LEAKAGE DURING ENGINE OPERATION AND REENTRY.

**MISSION PHASE: LO LIFT-OFF**

<b>VEHICLE/PAYLOAD/KIT EFFECTIVITY:</b>	102	COLUMBIA
	103	DISCOVERY
	104	ATLANTIS
	105	ENDEAVOUR

**CAUSE:**

PIECE PART STRUCTURAL FAILURE/SEAT LEAKAGE

**CRITICALITY 1/1 DURING INTACT ABORT ONLY? NO**

**REDUNDANCY SCREEN**

- A) PASS
- B) FAIL
- C) PASS

**PASS/FAIL RATIONALE:**

A)

B)

FAILS B SCREEN BECAUSE POSITION SWITCH INDICATION CANNOT BE USED TO DETERMINE VALVE POSITION. PIECE PART STRUCTURAL FAILURE MAY BE UNDETECTABLE BECAUSE POSITION SWITCHES ARE LOCATED IN THE ACTUATOR, NOT AT THE END OF THE VALVE DRIVE MECHANISM.

C)

**- FAILURE EFFECTS -**

**(A) SUBSYSTEM:**

LOSS OF REDUNDANCY DURING ASCENT TO PROTECT AGAINST OVERBOARD LEAKAGE OF PROPELLANT THROUGH THE FILL AND DRAIN LINE. WILL RESULT IN LOSS OF GHE SUPPLY DURING MANIFOLD REPRESS BECAUSE THE INBOARD VALVE REMAINS OPEN. THIS RESULTS IN LOSS OF THE AFT COMPARTMENT PURGE. LOSS OF AFT COMPARTMENT PURGE IS NOT CRITICAL (RESULTS IN POSSIBLE SYSTEM CONTAMINATION DURING ENTRY)

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0311-04**

**(B) INTERFACING SUBSYSTEM(S):**

SAME AS A.

**(C) MISSION:**

LOSS OF GHE SUPPLY HAS NO EFFECT (RESULTS IN POSSIBLE SYSTEM CONTAMINATION DURING ENTRY).

**(D) CREW, VEHICLE, AND ELEMENT(S):**

SAME AS A.

**(E) FUNCTIONAL CRITICALITY EFFECTS:**

1R/2 2 SUCCESS PATHS. TIME FRAME - ASCENT.

- 1) OUTBOARD FILL & DRAIN (PV9) FAILS TO REMAIN CLOSED.
- 2) INBOARD FILL & DRAIN VALVE (PV10) FAILS TO REMAIN CLOSED.

LO2 WILL DUMP OVERBOARD RESULTING IN LOSS OF PROPELLANT AND PREMATURE ENGINE SHUTDOWN. FIRE/EXPLOSIVE HAZARD EXTERIOR TO THE VEHICLE. POSSIBLE VIOLATION OF ET MINIMUM STRUCTURAL REQUIREMENTS DUE TO REDUCED ULLAGE PRESSURE. POSSIBLE LOSS OF CREW/VEHICLE.

---

**-DISPOSITION RATIONALE-**

---

**(A) DESIGN:**

VALVE IS BI-STABLE - WILL REMAIN IN LAST COMMANDED POSITION. AN INTEGRAL PART OF THE COPPER-BERYLLIUM ACTUATOR SHAFT IS A CAM WITH DETENTS IN THE OPEN AND CLOSED POSITION. THE CAM IS FOLLOWED BY A BELLVILLE - SPRING LOADED DETENT ROLLER. THE SEVEN STACKED BELLVILLES ARE SHIMMED, UPON INSTALLATION, TO PRODUCE A FORCE OF 140 LBS BY THE ROLLER UPON THE CAM, WHEN IN EITHER THE OPEN OR CLOSED POSITION. TO LEAVE EITHER POSITION THE ROLLER MUST PASS OVER A 0.105 INCH HIGH SHOULDER ON THE CAM. LOADED TANK PRESSURE TENDS TO FORCE THE GATE INTO GATE SEAL CONTRIBUTING TO AN EFFECTIVE SEAL AND TO HOLDING THE GATE CLOSED.

THE VALVE IS DESIGNED FOR 5000 LIFE CYCLES AND WAS CYCLED OPEN/CLOSED 5,653 TIMES (OVER 100 MISSIONS) DURING CERTIFICATION TESTING. CYCLING WAS AT BOTH CRYOGENIC AND AMBIENT TEMPERATURES AND WITH BOTH NORMAL AND ACCELERATED (SLAM) CYCLE TIMES.

**(B) TEST:**

ATP

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0311-04**

ANTI-SLAM VALVES (BEFORE ASSEMBLY INTO THE ACTUATOR) - EXAMINATION OF PRODUCT; AMBIENT PROOF (1275 PSIG); AMBIENT AND CRYO FLOW; AMBIENT AND CRYO CRACKING PRESSURE; POST TEST EXAMINATION.

ACTUATOR (BEFORE ASSEMBLY ONTO THE FILL AND DRAIN VALVE) - EXAMINATION OF PRODUCT; POSITION INDICATION; AMBIENT PROOF (1275); ELECTRICAL CHARACTERISTICS; AMBIENT EXTERNAL LEAKAGE.

RELIEF VALVE ASSEMBLY (BEFORE INSTALLATION INTO THE FILL & DRAIN VALVE)- EXAMINATION OF THE PRODUCT; AMBIENT PROOF (340 PSIG); AMBIENT AND CRYO CRACK/RESEAT (15-50 PSID) AND INTERNAL LEAKAGE; POST TEST EXAMINATION.

FILL AND DRAIN VALVE ASSEMBLY -

EXAMINATION OF PRODUCT

ELECTRICAL BONDING

AMBIENT PROOF WITH VALVE OPEN (358 PSIG) AND CLOSED (275 PSID) APPLIED AT INBOARD SIDE

CRYO PROOF WITH VALVE OPEN (358 PSIG) AND CLOSED (358 PSID) APPLIED AT INBOARD SIDE

AMBIENT AND CRYO EXTERNAL LEAKAGE OF VALVE BODY (270 PSIG)

CRYO EXTERNAL LEAKAGE OF ACTUATOR (740 PSIG)

AMBIENT AND CRYO RESPONSE TIME (NORMAL AT 400 AND 740 PSIG ACTUATOR PRESSURE, AND SLAM AT 740 PSIG)

AMBIENT AND CRYO ACTUATOR LEAKAGE FROM PORT TO PORT

AMBIENT AND CRYO VALVE SHAFT SEAL (PRIMARY AND SECONDARY) LEAKAGE WITH 270 PSID ACROSS THE SEAL

AMBIENT AND CRYO VALVE INTERNAL LEAKAGE (INLET-TO-OUTLET WITH 15 PSID, OUTLET-TO-INLET WITH 270 PSID)

AMBIENT AND CRYO RELIEF VALVE CRACK AND RESEAT (15 TO 50 PSID)

POST TEST EXAMINATION

CERTIFICATION

STRUCTURAL LOAD AT CRYO TEMPS (-300 DEG F) (AXIAL, SHEAR, TORSION, BENDING) WITH THE VALVE IN TENSION, PERFORM VALVE RESPONSE TIME (NOMINAL AND SLAM) ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), RELIEF VALVE CRACK AND RESEAT, AND EXTERNAL LEAKAGE (BODY AND ACTUATOR) TESTS. REPEAT WITH THE VALVE IN COMPRESSION.

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0311-04**

VALVE LIFE CYCLING:

2400 CYCLES AT AMBIENT TEMPERATURE WITH 5 PSIG INTERNAL PRESSURE (525 NORMAL CYCLES AND 1875 SLAM CYCLES)

100 AMBIENT CYCLES (50 NORMAL AND 50 SLAM CYCLES) WITH VALVE INLET VENTED TO ATMOSPHERE AND VALVE OUTLET CONNECTED TO A 4 CUBIC FOOT VOLUME PRESSURIZED TO 220 PSIG WITH GO2

2400 CRYO TEMPERATURE (-300 DEG F) CYCLES WITH 220 PSIG INTERNAL PRESSURE (1775 NORMAL CYCLES AND 625 SLAM CYCLES)

100 NORMAL CRYO CYCLES WITH THE VALVE INLET VENTED TO ATMOSPHERE AND THE OUTLET PRESSURIZED TO 220 PSIG

FOR THE FOREGOING LIFE TEST, PRIOR TO AND EVERY 100 CYCLES THEREAFTER, ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, AND VALVE INTERNAL LEAKAGE (OUTLET-TO-INLET) TESTS WERE PERFORMED.

RELIEF VALVE LIFE CYCLING :

2500 CYCLES AT CRYO (-300 DEG F) TEMP, 2500 CYCLES AT AMBIENT.

FOLLOWING EACH 500 CYCLES PERFORM FILL AND DRAIN VALVE INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), AND CRACK/RESEAT TESTS. POST CYCLE EXAMINATION.

VIBRATION:

PRE-VIBRATION TESTS -

VALVE RESPONSE TIME (NORMAL AND SLAM), ACTUATOR INTERNAL LEAKAGE, PRIMARY AND SECONDARY SHAFT SEAL LEAKAGE, INTERNAL LEAKAGE (OUTLET-TO-INLET AND INLET-TO-OUTLET), CRACK AND RESEAT, AND EXTERNAL LEAKAGE (BODY AND ACTUATOR)

TRANSIENT SINUSOIDAL VIBRATION -  
270 PSIG AND -250 DEG F IN EACH AXIS

RANDOM VIBRATION TESTS -

13.3 HOURS IN EACH OF THREE AXES WITH VALVE CLOSED AND AT -250 DEG F MAXIMUM. HALF OF THE TIME THE VALVE INTERNAL PRESSURE IS 270 PSIG; THE OTHER HALF AT 5 PSIG. ONCE EACH HOUR, CLOSING PRESSURE IS REMOVED FROM THE ACTUATOR. ALSO BOTH CLOSING AND OPENING PRESSURES ARE APPLIED CONCURRENTLY TO THE ACTUATOR. IN BOTH CASES THE VALVE REMAINS CLOSED

DESIGN SHOCK: 18 SHOCKS OF 15G EACH - THREE IN EACH DIRECTION ALONG EACH OF THREE AXES, ALL WITH VALVE OPEN AND ACTUATOR VENTED

DESIGN SHOCK POST TEST:

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0311-04**

AMBIENT - VALVE RESPONSE, INTERNAL AND EXTERNAL LEAKAGES CRYO - VALVE RESPONSE, INTERNAL AND EXTERNAL LEAKAGES ELECTRICAL CHARACTERISTICS; POSITION INDICATION

BURST: 413 PSIG VALVE OPEN 413 PSIG ON OUTLET OF CLOSED VALVE, 1700 PSIG ACTUATOR

GROUND TURNAROUND TEST  
ANY TURNAROUND CHECKOUT IS ACCOMPLISHED IN ACCORDANCE WITH OMRSD.

**(C) INSPECTION:**

RECEIVING INSPECTION

RAW MATERIALS ARE VERIFIED BY INSPECTION FOR MATERIAL AND PROCESS CERTIFICATION. BODY HOUSING FORGING IS ULTRASONICALLY AND PENETRANT INSPECTED.

CONTAMINATION CONTROL

PARTS ARE VERIFIED CLEAN TO LEVEL 800A. THE ACTUATOR IS CLEANED TO 400A.

ASSEMBLY/INSTALLATION

ALL PARTS ARE PROTECTED FROM DAMAGE AND CONTAMINATION. LOG OF CLEAN ROOM AND TOOL CALIBRATION ARE VERIFIED BY INSPECTION. ALL SURFACES REQUIRING CORROSION PROTECTION ARE VERIFIED. VISUAL (3X TO 7X) AND DIMENSIONAL INSPECTION OF VALVE BODY AND COMPONENTS ARE VERIFIED DURING ASSEMBLY. THREADED FASTENER TORQUES ARE VERIFIED BY INSPECTION. MANDATORY INSPECTION POINTS ARE INCLUDED IN THE ASSEMBLY PROCEDURE.

CRITICAL PROCESSES

HEAT TREATMENT AND DRY FILM LUBE APPLICATION ARE VERIFIED BY INSPECTION.

NON DESTRUCTIVE EVALUATION

VALVE BODY, PRIOR TO FINAL MACHINING, IS SUBJECTED TO DYE PENETRANT INSPECTION. REQUIREMENTS FOR DETAIL PARTS PENETRANT INSPECTION ARE BASED UPON CONFIGURATION, MATERIAL, AND MANUFACTURING PROCESSES.

TESTING

ACCEPTANCE TEST VERIFIED BY INSPECTION.

HANDLING/PACKAGING

PACKAGING FOR SHIPMENT VERIFIED BY INSPECTION.

**(D) FAILURE HISTORY:**

CURRENT DATA ON TEST FAILURE, FLIGHT FAILURE, UNEXPLAINED ANOMALIES, AND OTHER FAILURES EXPERIENCED DURING GROUND PROCESSING ACTIVITY CAN BE FOUND IN THE PRACA DATABASE.

**(E) OPERATIONAL USE:**

**FAILURE MODES EFFECTS ANALYSIS (FMEA) -- CIL FAILURE MODE  
NUMBER: 03-1-0311-04**

ON GROUND CALL, CREW CAN CLOSE INBOARD FILL AND DRAIN VALVE FOR ENTRY, IF  
DETECTABLE (POSITION INDICATION) AND TIME PERMITS.

---

**- APPROVALS -**

---

S&R ENGINEERING	: W.P. MUSTY	: /S/ W. P. MUSTY
S&R ENGINEERING ITM	: P. A. STENGER-NGUYEN	: /S/ P. A. STENGER-NGUYEN
DESIGN ENGINEERING	: STUART KOBATA	: /S/ STUART KOBATA
MPS SUBSYSTEM MGR.	: TIM REITH	: /S/ TIM REITH
MOD	: BILL LANE	: /S/ BILL LANE
USA SAM	: MIKE SNYDER	: /S/ MIKE SNYDER
USA ORBITER ELEMENT	: SUZANNE LITTLE	: /S/ SUZANNE LITTLE
NASA SR&QA	: BILL PRINCE	: /S/ BILL PRINCE