EA/CIL REDUNDANCY SCREEN

Component Group:

Ducts and Lines

CIL Item: Part Number: K223-01 RS007365

Component:

LPOTP Discharge Pressure Transducer Line

FMEA Item:

Failure Mode:

K223 Fails to contain oxidizer. Prepared:

Approved:
Approval Date:
Change #:
Directive #;

D. Early T. Nguyen 7/25/00

CCBD ME3-01-5638

Page:

1 of 1

Phase	Failure / Effect Description	Criticatity Hazard Reference
PSMCD 4.1	Oxidizer leakage into aft compartment. Overpressurization of aft compartment. Loss of vehicle.	1
	Redundancy Screens: SINGLE POINT FAILURE: N/A	ME-C3P,D, ME-C3S, ME-C3M, ME-C3A,C

SSME FMEA/CIL DESIGN

Component Group:

Ducts and Lines

CIL Item: Part Number: K223-01 RS007365

K223

Component:

LPOTP Discharge Pressure Transducer Line

FMEA Item:

Failure Mode:

Fails to contain oxidizer.

Prepared:

D. Early

Approved: Approval Date: T. Nguyen 7/25/00

Change #:

1

1 of 1

Directive #:

CCBD ME3-01-5638

Page:

je:

Design / Document Reference

FAILURE CAUSE: A: Parent material failure or weld failure.

THE LINE ASSEMBLY (1) IS MANUFACTURED UTILIZING 321 CRES TUBE AND INCONEL 625 BAR. 321 CRES TUBING WAS SELECTED BECAUSE OF ITS STRENGTH, FABRICABILITY, GENERAL CORROSION RESISTANCE, AND STRESS CORROSION RESISTANCE (2). INCONEL 625 WAS SELECTED FOR ITS WELDABILITY, FORMABILITY, RESISTANCE TO STRESS CORROSION CRACKING, AND CORROSION RESISTANCE (2). INCONEL 625 POSSESSES THE REQUIRED STRENGTH WITHOUT REQUIRING HEAT TREAT. ALL MATERIALS USED IN THE LINE FABRICATION ARE LOX COMPATIBLE (2). FLANGE SECTIONS INCORPORATE RADIUS JOINTS TO REDUCE STRESS CONCENTRATIONS. OFFSET LIMIT REQUIREMENTS ARE ESTABLISHED TO REDUCE STRESS CONCENTRATIONS AND IMPROVE WELD GEOMETRY. TUBING STOCK IS DRAWN TO MAINTAIN SURFACE REGULARITY. INSTALLATION IS CONTROLLED FOR ANGULARITY AND OFFSET PER SPECIFICATION REQUIREMENTS (3). MINIMUM FACTORS OF SAFETY FOR THE LINE MEET CEI REQUIREMENTS (4). HIGH AND LOW CYCLE FATIGUE LIFE MEET CEI REQUIREMENTS (5). THE LINE ASSEMBLY HAS COMPLETED PRESSURE CYCLING AND ULTIMATE PRESSURE DVS TESTING (6). THE LINE ASSEMBLY PARENT MATERIALS WERE CLEARED FOR FRACTURE MECHANICS/NDE FLAW GROWTH, SINCE THEY ARE NOT FRACTURE CRITICAL PARTS (7). TABLE K223 LISTS ALL THE FMEA/CIL WELDS AND IDENTIFIES THOSE WELDS IN WHICH THE CRITICAL INITIAL FLAW SIZE IS NOT DETECTABLE, AND THOSE WELDS IN WHICH THE ROOT SIDE IS NOT ACCESSIBLE FOR INSPECTION. THESE WELDS HAVE BEEN ASSESSED AS ACCEPTABLE FOR FLIGHT BY RISK ASSESSMENT (8).

(1) RS007365; (2) RSS-8582, RSS-8575; (3) RA1102-006; (4) RSS-8546, CP320R0003B; (5) RL00532, CP320R0003B; (6) SSME-81-1046; (7) NASA TASK 117; (8) RSS-8756

INSPECTION AND TEST

Component Group:

Ducts and Lines

Fails to contain oxidizer.

CIL Item: Part Number:

K223-01 RS007365

Component:

FMEA Item:

Failure Mode:

LPOTP Discharge Pressure Transducer Line

Prepared: Approved: D. Early T. Nguyen

Approval Date: Change #:

7/25/00

Directive #:

CCBD ME3-01-5638

Page:

1 of 1

			1011
Failure Causes	Significant Characteristics	Inspection(s) / Test(s)	Document Reference
A	LINE FLANGE PLATE		RS007365 RS007361 RS007342
	MATERIAL INTEGRITY	MATERIAL INTEGRITY IS VERIFIED PER DRAWING REQUIREMENTS.	RS007365 RS007361 RS007342
		DETAILS ARE PENETRANT INSPECTED PER SPECIFICATION REQUIREMENTS.	RA0115-116
	WELD INTEGRITY	ALL WELDS ARE INSPECTED TO DRAWING AND SPECIFICATION REQUIREMENTS PER WELD CLASS. INSPECTIONS INCLUDE: VISUAL, DIMENSIONAL, PENETRANT, RADIOGRAPHIC, ULTRASONIC, AND FILLER MATERIAL, AS APPLICABLE.	RL10011 RA0607-094 RA0115-116 RA0115-006 RA1115-001 RA0115-127
	ASSEMBLY INTEGRITY	THE ASSEMBLY IS PROOF PRESSURE TESTED PER DRAWING REQUIREMENTS.	RS007365
	FLIGHT FLOW TESTING	THE EXTERNAL SURFACE IS VISUALLY INSPECTED PRIOR TO EACH LAUNCH.	OMRSD V41BU0.030
		A HELIUM SIGNATURE LEAK TEST IS PERFORMED PRIOR TO EACH LAUNCH. (LAST TEST)	OMRSD S00000.950

Failure History:

Comprehensive failure history data is maintained in the Problem Reporting database (PRAMS/PRACA)

j

Reference: NASA letter SA21/88/308 and Rocketdyne letter 88RC09761.

Operational Use:

Not Applicable.

SSME FMEA/CIL WELD JOINTS

Component Group: CIL Item:

Ducts and Lines

Part Number:

K223 RS007365

Component:

LPOTP Discharge Pressure Transducer Line K223

FMEA Item:

Prepared:

D. Early

Approved:

T. Nguyen 7/25/00

Approval Date: Change #: Directive #:

CCBD ME3-01-5638

		:						
<u> </u>		<u> </u>					Page:	1 of 1
					Root Side Not	Critical Initial Flaw Size Not Detectable		
Component	Basic Part Number	Weld Numbe	r Weld Type	Class	Access	HCF LCF	Co	omments
LINE	RS007367	1,2	GTAW	1	X	X		